

Specifications

Details	
Product code	RBSXTsqG-5acD
Architecture	ARM 32bit
CPU	IPQ-4018
CPU core count	4
CPU nominal frequency	716 MHz
Dimensions	129 x 129 x 34 mm
RouterOS license	3
Operating System	RouterOS
Size of RAM	256 MB
Storage size	16 MB
Storage type	FLASH
MTBF	Approximately 100'000 hours at 25C
Tested ambient temperature	-40°C to 70°C
IPsec hardware acceleration	Yes

Powering

Details	
Number of DC inputs	1 (PoE-IN)
Max power consumption	7 W
Cooling type	Passive
PoE in	Passive PoE
PoE in input Voltage	10-28 V

Wireless specifications

Details	
Wireless 5 GHz Max data rate	867 Mbit/s
Wireless 5 GHz number of chains	2
Wireless 5 GHz standards	802.11a/n/ac

Details

Antenna gain dBi for 5 GHz	16
Wireless 5 GHz chip model	IPQ-4018
Wireless 5 GHz generation	Wi-Fi 5

Ethernet

Details

10/100/1000 Ethernet ports	1
----------------------------	---

Certification & Approvals

Details

Certification	CE, FCC, IC, EAC, ROHS
IP	IP54

Wireless specifications

5 GHz	Transmit (dBm)	Receive Sensitivity
6MBit/s	25	-96
54MBit/s	21	-80
MCS0	25	-96
MCS7	20	-75
MCS9	18	-70